

Session 1: EI Preparation for Modeling

Emission Inventories and Modeling Activities for the Development of Air Quality Plans in Madrid (Spain)

R. Borge, J. Lumbreras, J. Pérez, D. de la Paz,
M. Vedrenne, E. Rodriguez

*Laboratory of Environmental Modelling
Technical University of Madrid (UPM)*

rborge@etsii.upm.es


Tampa, Florida. August, 16th

OUTLINE

1. Introduction
 2. Air Quality Modeling system
 3. Emission Inventories
 4. Applications and Results
 5. Conclusions
-



1. INTRODUCTION

- Modelling is an essential tool for the development of emission abatement measures and air quality plans
- These plans are often related to urban environments
- Air quality modelling in urban areas is very complex:
 - ✓ Multiple pollutants
 - ✓ Multiple sources
 - ✓ Multiple spatial/temporal scales
 - ✓ Model policies and measures (e.g. NO₂)



**Requirements for
the modeling
system and
emission
inventory**

Case study




Annual evolution of NO₂ levels (average of a number of representative stations in Madrid)

- Madrid city (Spain): 3.4 million inhabitants in the city, more than 5 million people in the metropolitan area
- Positive trend of AQ in the city. Remaining issues: NO₂


2. AIR QUALITY MODELING SYSTEM

● Mesoscale modeling system



- Four nested domains can consistently describe air pollution processes from continental to urban scale
- Suitable to estimate contributions from different geographic areas (international, national, regional and local)





Domain	Spatial resolution (km)	Dimensions (km)		Vertical levels
		x	y	
D1	48	6144	5376	30
D2	16	1200	960	
D3	4	192	192	
D4	1	40	44	



- The system is able to depict urban background levels (e.g. NO₂)

Relative Directive Error (RDE)
Directive 2008/50/EC

$$RDE = \frac{|O_{LV} - M_{LV}|}{LV} *$$



NO₂ uncertainty (MRDE)

Hourly VL = 23,7 %


Annual VL = 22,4 %

- Acceptable performance
(MB = -2.2 µg/m³;
r = 0.63; MFB = -14.1%...)

* where O_{LV} is the closest observed concentration to the limit value concentration (LV) and M_{LV} is the correspondingly ranked modelled concentration. The maximum of this value found at 90% of the available stations is then the Maximum Relative Directive Error (MRDE).

- However, some pollutants such as NO_2 present strong concentration gradients that can not be reproduced by Eulerian models


SERCA project. Passive sampling field campaign June-July 2009



Hot spot modeling: OSPM (street canyon model)



Outputs from CMAQ (subtracting street contribution to avoid double counting)






RDE hourly LV = 5 %

RDE annual LV = 13 %

$MB = 5,0 \mu\text{g}/\text{m}^3$ $ME = 22,8 \mu\text{g}/\text{m}^3$

$r = 0,665$




3. EMISSION INVENTORIES


- Key input to air quality models:
 - ✓ One of the main sources of uncertainty (emission estimate and EI preparation for modeling)
 - ✓ Emission abatement as the only way to improve air quality
- Requirements / basic design criteria:
 - ✓ Compatible with AQM requirements
 - ✓ Consistency across the scales / models
 - ✓ Flexible and detailed enough to reflect the outcome of relevant measures \Rightarrow complete and proportionate
 - ✓ Adaptation to SMOKE framework / concepts

● D1 (Europe)

- EMEP inventory for anthropogenic emissions (built from national submissions under the Convention on Long-range Transboundary Air Pollution, LRTAP)




- GEIA for biogenic VOC emissions (Guenther algorithms: computation as well as temporal and spatial allocation)



● D2 (Iberian Peninsula)

- Integration of official National Emission Inventories of Spain (SNEI) and Portugal (PNEI):
 - 184 area-source categories and 62 point-source categories (1720 stacks)
 - more than 300 temporal profiles
 - more than 200 chemical profiles for VOCs, NO_x and PM_{2.5} (EMEP/EEA guidebook and USEPA ESPECIATE)




● D3 (Greater Madrid Region)

- Combination of two official EI:

- regional estimates from SNEI
- Madrid Region Inventory


- Comprehensive analysis, harmonization and assessment through AQ modeling:

- computation methods
- activity data
- ancillary information




● D4 (Madrid metropolitan area)






- Ad-hoc inventory that combines official estimates and highly detailed specific bottom-up estimates for the most relevant sectors:



Grupo SNAP	CO	NH3	NOX	PM10	PM25	SO2	VOC	ISOP	TERP	OVOC
1	225	0	243	50	29	1128	1	0	0	0
2	10004	0	3680	520	410	2731	1104	0	0	0
3	2238	0	10689	265	210	2494	1217	0	0	0
4	1083	130	108	51	32	70	3782	0	0	0
5	0	15	0	0	0	0	2056	0	0	0
6	0	212	0	0	0	0	48828	0	0	0
7	59712	496	32102	1736	1452	147	14205	0	0	0
8	2711	0	4171	360	360	287	769	0	0	0
9	441	2036	1769	26	26	6	5267	0	0	0
10	357	1543	56	90	13	0	17	0	0	0
11	32	605	125	0	0	0	233	1013	2574	862
TOTAL D4	76803	5037	52942	3098	2533	6863	77479	1013	2574	862




- Key feature: integration with the regional traffic model (TDM) for emission computation at link level (15 000 aprox.)



Zonas	Autobuses	Pesados	Taxis	Motos	Ciclomotores	Ligeros	Turismos
Interior 1º cint.	4,84%	7,42%	15,91%	6,08%	1,21%	5,25%	59%
En el 1º cint.	2,22%	6,43%	13,32%	3,59%	0,72%	5,68%	68%
Entre 1º y 2º cint.	2,77%	5,95%	15,25%	4,62%	0,92%	5,59%	65%
En el 2º cint.	2,67%	5,70%	8,33%	2,73%	0,54%	5,76%	74%
Entre 2º cint. Y M-30	1,93%	5,58%	9,18%	3,54%	0,71%	5,76%	73%
En la M-30	1,53%	6,26%	3,88%	1,80%	0,00%	8,86%	77,67%
Entre M-30 y M-40	2,58%	7,56%	5,78%	2,27%	0,45%	5,68%	76%
En la M-40	2,58%	7,56%	5,78%	2,72%	0,00%	5,68%	75,67%
Exterior a la M-40	2,58%	7,56%	5,78%	2,27%	0,45%	5,68%	76%

- Hourly resolved intensity and speed from the traffic model at link level
- Vehicle mix (types) from the traffic model at management area level
- Fleet characterization (age and technology) from field campaigns



- Emissions computation according to COPERT (only urban driving pattern). Modeling in SMOKE:
 - ✓ 63 inventory categories (7 vehicle types x 9 management areas)
 - ✓ 63 NO_x speciation profiles and 9 VOC speciation profiles (COPERT)
 - ✓ 9 (management areas) spatial surrogates (by grid overlapping)

- This design incorporates all the information available and allows the simulation of any of the potential measures for the sector:


-Low emission zones (access restrictions by vehicle type, age or technology)

-Speed limits




-Penetration of new technologies (combustion engines standards, hybrid and electric vehicles, etc.)

-Specific fleet turnover and limitations by segments (buses, taxis, light duty vehicles, passenger cars, etc.)

-Measures to alleviate urban congestion



Impact on the variables/parameters involved in emission computation





3. APPLICATIONS AND RESULTS

- Source apportionment (sensitivity analysis):
 - ✓ Basic emission abatement strategy / course of action
 - ✓ Maximum feasible AQ improvement related to the main emitting sectors
 - ✓ Quantification of external constraints
 - ✓ Legal requirement to apply for the NO₂ compliance postponement
- Basic methodology: zero-out:
 - ✓ Comparison of on/off model results for a particular sector
 - ✓ Comparison of model results with alternative BC and geographical masks

- E.g. contribution of local road traffic - emissions


NO emissions (all sources)

NO emissions (excluding road traffic in Madrid city)




- E.g. contribution of local road traffic – model response (NO_2 concentration)

Base or reference




No local road traffic




- E.g. contribution of local road traffic – comparison and apportionment

Absolute




Relative




- In general, Madrid is strongly dominated by local sources, mainly road traffic
- National and international influence is negligible

**Madrid average concentration =
28,1 $\mu\text{g}/\text{m}^3$**



**Apportionment to NO_2 annual
average ($\mu\text{g}/\text{m}^3$)**



Local sources (municipality)
External sources


Measures aimed
at limiting local
road traffic with
an additional
effect at regional
level
(metropolitan
area)

● Scenario development and assessment

- Main considerations for the development of future-year scenarios:
 - ✓ abatement measures focused on the emission sectors responsible for air pollution (according to the source apportionment study)
 - ✓ emission projection model consistent with emission model/methods used for the reference year
 - ✓ transparency and documentation, highlighting critical hypotheses and parameters


- Madrid Air Quality Plan (for NO₂ compliance by 1st January 2015)

- Up to 70 abatement measures have been assessed and evaluated
- A global decrease of 31% in NO_x emissions is expected, mainly due to measures in the road transport sector (40% decrease)



● Outputs (air quality):



- Compliance expected before 2015
- Results to be complemented by microscale measures / modelling



-Annual NO₂ levels reduced by 34% as an average; approximately 15 µg/m³ in the city center

-Important impact in the metropolitan area (-7 µg/m³ as an average in the modeling domain)

- The AQ Plan assessment includes some additional measures intended for pollution episodes, such as exceptional restrictions for application in the LEZ



Impact of passenger cars access restriction by 20% (a) and 50% under unfavorable meteorological conditions (24-h average NO₂)

5. CONCLUSIONS

From the case study

- Meeting the Limit Value (LV) for NO₂ in urban environments is a rather challenging issue
- NO₂ ambient concentration values in Madrid are strongly dominated by local sources with a remarkable contribution from road traffic
- According to the results of this study, cutting down NO_x emissions by 31% would allow the fulfillment of NO₂ limit values in Madrid by the end of 2014
- Further modeling activities are needed to assess complementary microscale measures in specific hot spots

General

- The analysis and design of Urban Air Quality Plans (UAQP) is a very complex task that has to be supported by suitable air quality modeling tools
- Emission inventories play a critical role in the development of UAQP. They should meet a series of requirements:
 - Consistency across the scales, air quality models and projection methods
 - Flexible and detailed enough to accurately reflect the effect of any abatement option
- The SMOKE modeling system has been proved a useful tool to support this kind of development for the Madrid Metropolitan Area



20th USEPA International Emission Inventory Conference.
August 13-16, 2012. Tampa (Florida)



Thank you for your attention!

rborge@etsii.upm.es